



PRODUCT-DETAILS

XT1N 125 TMF 20-500 3p F F UL/CSA
XT1N 125 TMF 20-500 3p F F UL/CSA



General Information	
Extended Product Type	XT1N 125 TMF 20-500 3p F F UL/CSA
Product ID	1SDA074635R1
EAN	8015644785024
Catalog Description	XT1N 125 TMF 20-500 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT1N 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 20-500 A

ABB EcoSolutions	
ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	9AKK108468A2347
Environmental Product Declaration - EPD	9AKK108468A1890
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 55.9 %

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Declaration	9AKK108466A1424
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	dec62d62-6ff8-4fd2-8029-325c859957a2 Italy
Simplified SCIP	7fba01c1-2957-4780-94cb-294c13410fdf Germany 7cdb3ac7-8d65-4c68-a008-7f3236b6b7e4 Norway b19c6afe-cd1c-4b56-bc4c-fdcb4c601d0f Finland 1dc041df-a6d3-4974-801b-c949e9ea9b61 Netherlands b5d6ffe7-8bee-4257-8b45-74b65beaa3f8 Poland fe746a16-34a6-41f6-a520-5145153ca52a Netherlands 4b27289a-e553-40c1-a568-0c4215ab4ff7 Netherlands 84d2843e-fbaa-4365-8ef1-00bafbe03ce8 Estonia 2b3fd3de-10f3-4af4-bcb0-8e8d64cbc1a2 Bulgaria 22cc68c5-3b61-4e6f-b014-28ecc301f71e Sweden 53e2deed-c41d-45fe-91e1-13281b7bda5a Poland 74b98179-2c8f-4574-aedf-69ce3334e6fd France 1df07802-e6b0-4a45-8d79-5ec17bcb43d4 Sweden 293667d5-0724-421c-b235-d662565da8a1 Germany 6d1b3908-017d-488b-911e-8bbb9da68345 Germany ced8d5e8-6d10-43d5-8eec-9ff55abb8741 Germany 8b9dd373-a329-4430-a6ab-fe267fca92c6 Denmark e7b5e2fa-d1d7-49e6-abd5-7b85c0011343 Germany 8864f15c-94b2-4097-9f64-2ea91e2f165e Croatia e994f49c-1ba9-46ad-81a5-4d636336b11b Czech Republic 2003fa25-d6ad-4589-bd12-42dcc0fc9968 Poland 1b8b579f-67c3-4a06-a53c-afee0cbde876 Portugal eaf928c2-5475-4ee7-a9d7-7fb8062eec9c France ee5b69f7-3429-4c1a-9b6a-4f0978d641f1 Netherlands 27345f4c-df1a-4cb9-a024-9c205de2a911 Spain 9e891527-578c-4ac2-9bd4-16bd92f653d7 Netherlands 717a8935-7a0f-4bb0-b511-6053c4e75da6 Greece

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

Order Code US and Canada	XT1NU3020AFF000XXX
EAN	8015644785024
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	8015644785024

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Suitable for Product Class	SACE Tmax XT
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Technical

Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm ²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3P
Opening Time	CB with SOR 30 ms CB with UVR 30 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 1.8 W
Rated Current (I_n)	20 A
Rated Instantaneous Short-Circuit Current Setting (I_i)	500 A
Rated Operational Voltage	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I_u)	125 A
Rated Voltage (U_r)	600Y/347 V
Recommended Screw Driver	Main Circuit M6
Release	TMF
Release Type	TM
Setting Range	20 A
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT1

Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA (480 V AC) 25 kA (600Y / 347 V AC) 18 kA (250 V DC) 2 Poles in Series 35 kA (500 V DC) 4 Poles in Series Kind 35 kA
-----------------------------------	--

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3905
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5532
UL Certificate	1SDL000163R0111
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0003

External Classifications and Standards

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

